

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ CERTIFICATO DA DNV = ISO 9001 =

b.o.b. Sistemi Idraulici S.p.A.





Technical features

- Twin telescopic arms run mm 1.400
- L1: Lifting capacity at ground level ton 18
- L2: Lifting cap. extended arms tons 12,5
- L3: Lifting cap. 800 mm under level ton 12,5
- L4: Lifting cap 800 mm under the ground level with extended arms ton 8
- No. 4 flow controls with ground hand levers
- Rear independent stabilizing feet
- Tipping hooks with ground control
- Front oil tank with support frame
- Adjustable platform wedges
- Painting antirust red or grey chassis colour
- Operation manual and spare parts book
- Basic equipment weight: kg 3.450 ca.*)

Special Options

- Independent telescopic arms
- Sheathing system flow control add.sections
- Platform length mm 5.000

Standard Options

- Standard integrated subframe H 180 mm
- No. 4 adjustable chains with safety hook locks
- Front cab protection panel
- Mech. security on tipping hook (DIN 30720)
- Landing feet rollers
- Hoisting cylinders rods protection carter
- Regenerating oil system (double speed)
- Cab controls on mobile hand-board
- Radio control
- Monitoring led arms in resting position
- Monitoring led for stabilizing feet
- Visual or sonorous signalling of tipping hooks position
- Rear lights integrated in the headstock carter
- Pull down platform access ladder
- Rear working lights

*) The weight is indicative and referred to the basic skip loader without options, accessories and ancillary equipments (platform extension, front cab protection, cylinders protection carter, rear headstock protection carter, etc.)







The technical details shown in this sheet are indicative and can be changed by the builder without prior notice. **B.O.B. Sistemi Idraulici S.p.A.** – Regione Oltre Rea, 32 – 12060 Monchiero (CN) - Italia P. I.V.A. 00496180043 - Tel.: +39 (0173) 780002/3 – Fax: +39 (0173) 780004 Internet: www.bobspa.com - E-mail: info@bobitalev.com